

PT-QU

Quadro Porcelain Paver



Overview

The Quadro Porcelain Paver is a 20mm porcelain tile with a minimalist, contemporary concrete design, featuring subtle screed lines and cementitious textures. This popular porcelain slab comes in three warm tones and is available in two formats, providing various design options to complete a clean, modern, and inviting aesthetic. This high-end ceramic paver is durable, low maintenance, and non-porous, making it perfect for functional yet beautiful environments.



- Rigorously slip-tested and certified as low-risk of slip
- Environmentally safe, eco-friendly, and sustainable
- CE Marked
- 3 colour options
- Various size options

Details

Material	Ceramic
Dimensions	600x600mm 600x1200mm
Working dimensions	597x597mm 597x1195mm
Weight	44.8kg/m ²
Light Reflectance Value (LRV)	See “Part information” below
Number of face patterns	See “Part information” below

Performance

Reaction to fire (BS EN 13501-1)	Inherently A1 (Decision 94-611/EC)
Performance - Reaction to fire (BS EN 13501-5)	B ^{ROOF} (t4)*
Slip resistance (BS EN 7976)	Classification: Low Slip Potential Slider 55 (Dry): >102 PTV Slider 55 (Wet): >43 PTV Slider 96 (Dry): >64 PTV Slider 96 (Wet): >54 PTV
Allowable load	See “Compatible system” data below
Breaking strength (ISO 10545-4)	≥9.5kN
Repeated shock test (installation on pedestals)	QB UPEC F+ compliant

* When installed as part of a complete RYNO system

Part information

Size	Colour	LRV	Pack quantity	Pallet quantity
600x600mm	Crema Beige	48	2	64
600x600mm	Argento Grey	33	2	64
600x600mm	Nero Anthracite	16	2	64
600x1200mm	Crema Beige	48	2	32
600x1200mm	Argento Grey	33	2	32
600x1200mm	Nero Anthracite	16	2	32

Finishes















Please note: Colour shades may differ between batches. If you need a specific batch to match a previous order for a project, please inform us when placing your order, although availability can't be guaranteed.







Got questions? Give us a shout.

Visit www.rynosystems.com or call us today on **+44 (0)203 967 3500** or reach out on sales@rynosystems.com

Compatible components

	RP-FR Non-Combustible Adjustable Paving Support Pedestal		RPA-FR Non-Combustible Self-levelling Paving Support Pedestal
	RPS-FR Non-Combustible Stackable Paving Support Pad		RP-FR-WU Non-Combustible Wind Uplift Paving Support Pedestal
	RPS Stackable Paving Support Pad		RPA Self-levelling Adjustable Paving Support Pedestal
	RPF Fixed Head Adjustable Paving Support Pedestal		RPF-LH Low-Height Adjustable Paving Support Pad
	RST Aluminium Paving Support Rail		FA Furniture Anchor
	HRSP Self-Adhesive Head Rubber Shock Pad		RHF-WU Rail Wind Uplift Restraint - Hidden Fixing
	ESC Edge Spring Clip		PSR Rail Paving Spacer

Compatible systems

 TerraSmart® Pedestal Paving System Straightforward, robust paving system for waterproofed substrates	 TerraSmart® Pedestal Paving System Straightforward, robust paving system for waterproofed substrates, where non-combustibility isn't required	 TerraSmart® Rail Paving System Premium, versatile paving system for waterproofed substrates
 TerraSmart® Rail Paving System Premium, versatile paving system for waterproofed substrates, where non-combustibility isn't required	 BalcaSmart® Rail Paving System Premium, versatile paving system for waterproofed substrates	 BalcaSmart® Pedestal Paving System Straightforward, robust paving system for metal-frame balconies

Got questions? Give us a shout.

Visit www.rynosystems.com or call us today on **+44 (0)203 967 3500** or reach out on sales@rynosystems.com

Annex 2

Manufacturing tolerances

Detail	Value	Standard
Length and width	$\pm 0.3\%$ / $\pm 1\text{mm}$ (*)	ISO 10545-2
Thickness	$\pm 5\%$ / 0.5mm (**)	ISO 10545-2
Straightness of sides	$\pm 0.2\%$ (***)	ISO 10545-2
Rectangularity	$\pm 0.2\%$	ISO 10545-2

Thermo-hygrometric properties

Detail	Value	Standard
Thermal shock resistance	Pass - Resistant	ISO 10545-9
Freeze/Thaw resistance	Pass - Resistant	ISO 10545-9
Frost resistance	Pass - Resistant	ISO 10545-12

Other properties

Detail	Value	Standard
Water absorption level (in% by mass)	$\leq 0.1\%$	ISO 10545-3

(*) The permissible deviation, in % or mm, of the average size for each tile (2 or 4 sides) from working dimension.

(**) The permissible deviation, in % or mm, of the average thickness for each tile from working dimension.

(***) The maximum permissible deviation from straightness, in % or mm, related to the corresponding working dimension