

Nimra

Riven Concrete Paving



Overview

Nimra riven concrete paving provides a versatile paving option to complement most spaces including terraces, balconies, and access walkways. These riven concrete pavers are available in two individual finishes to suit your project. Featuring a riven finish, and advanced fibrous technology, the Nimra range feels like a topographical map with its soft mountainous ridges and valleys.

Key Features:

- Two colour options
- Complies with BS EN 1339:2003
- Non-combustible - A1 rated
- Available in two sizes



Description

Appearance	Solid unit with riven profile
Manufacturing Process	Hydraulically pressed concrete
Base Raw Material	Concrete
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1339 : 2003

Physical Properties

Tolerances on Work Dimensions (mm)	Length ± 2 mm, width ± 2 mm, thickness ± 3 mm
Abrasion Resistance (mm)	≤ 23 mm (Wide Wheel Abrasion Test)
Durability (Freeze-thaw) \leq	≤ 1.0 kg/m ² as a mean with no individual value > 1.5 kg/m ²
Material Density	2300 kg/m ³ (typically)
Slip/Skid Resistance (polished)	Mean polished skid resistance value (PSRV) : > 45
Slip/Skid Resistance (unpolished)	Mean unpolished skid resistance value (USRV) : > 45 .
Thermal Conductivity (K value)	Design data as defined to BS EN 13369 : 2013

Specification

Emission of Asbestos	No content
Reaction to fire	A1 and Afl
Breem	These units can achieve an "A" rated system when used in conjunction with the correct sub-base components
Carbon Footprint	13 kg CO ₂ m ²

Size Range

Nominal Dimensions (mm)	Approx. Weight (KG)	Pack Qty	Pack Weight (KG)
450 x 450 x 50	23	40	936
600 x 600 x 50	42	20	842

Further Information

Cleaning & Maintenance	Available on request
Efflorescence	Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking.
Weathering	It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Product Evolution	The evolution of new product design is continuous, and information is subject to change without notice. Customers should check with the supplier to ensure that they have the latest details. Ryno reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice.
Chemical Incompatibilities	
Recommended End of Life Disposal	

Colours



Riven Natural

450 x 450 x 50mm
600 x 600 x 50mm



Riven Buff

450 x 450 x 50mm
600 x 600 x 50mm

Got questions?

Speak to one of our expert advisors

Visit www.rynogroup.co.uk or call us today on **+44 (0)203 967 3500** or reach out on sales@rynogroup.co.uk.

Compatible Systems

 <p>TerraSmart® Pedestal Paving System</p> <p>Straightforward, robust paving system for waterproofed substrates</p>	 <p>TerraSmart® Rail Paving System</p> <p>Premium, versatile paving system for waterproofed substrates</p>	<p>TerraSmart® Rail Paving System</p> <p>Premium, versatile paving system for waterproofed substrates, where non-combustibility isn't required</p>
<p>TerraSmart® Pedestal Paving System</p> <p>Straightforward, robust paving system for waterproofed substrates, where non-combustibility isn't required</p>	 <p>BalcaSmart® Pedestal Paving System</p> <p>Straightforward, robust paving system for metal-frame balconies</p>	 <p>BalcaSmart® Rail Paving System</p> <p>Premium, versatile paving system for waterproofed substrates</p>

Got questions?

Speak to one of our expert advisors

Visit www.rynogroup.co.uk or call us today on **+44 (0)203 967 3500** or reach out on sales@rynogroup.co.uk.