

RVF-WU

Rail Wind Uplift Restraint - Visual Fixing



Overview

The Rail Wind Uplift Restraint - Visual Fixing is a subtle stainless steel component that provides wind uplift restraint for RYNO® porcelain pavers when used with the RST Aluminium Paving Support Rail. The bottom washer locks into the RST rail, while the dome head fixing and sleek stainless steel washer securely connects the paving surface to the rail.

- Secure wind uplift restraint
- Subtle fixing detail
- Simple installation
- A4 stainless steel



Details

Material	Flange Head Fixing: Stainless Steel A4 Top Washer: Stainless Steel A4 Bottom Fixing Nut: Stainless Steel A4
Dimensions	M4 x 35mm
Drive type	Hex drive
Details Column Title 3	Associated Value

Performance

Cyclic wind load testing (EOTA Technical Report TR005:2003)	Product tested to a maximum of 6000 Pascals in pulsed cycles. No detrimental effects to any of the system were found and no failures were observed during testing.
Reaction to fire (BS EN 13501-1)	Inherently A1 (Decision 94-611/EC)
Biological and chemical	Suitable for category C5 - Industry and coastal areas with high humidity and aggressive atmosphere. Constant condensation and heavily polluted atmosphere.
Warranty	30 years*
Design life	60 years

*when used as part of a complete RYNO IGNO system

Compatible Components

	RST Aluminium Paving Support Rail		PT-QU Quadro Porcelain Paver
---	--	--	---

Got questions? Give us a shout.

Visit **www.rynosystems.com** or call us today on **+44 (0)203 967 3500** or reach out on **sales@rynosystems.com**