

PDSR Rail Paving Drainage Spacer



Patent Granted: GB 2581209

Overview

The Rail Paving Drainage Spacer performs 2 important functions. It is designed to act as a device that breaks the surface tension of water on the tile, draining surface water nearly 10x quicker than it would without the device. It is a compatible spacer for the RST Aluminium Paving Support Rail, available in T, straight, and cross configurations to accommodate different paving layouts. This robust black plastic product doubles up as a paving spacer, featuring an innovative twist-lock base that slots neatly into the RST rail for seamless and satisfying installation.

- Mitigates algae build up by quickly dissipating surface water
- Dissipates up to 97% surface water in 1 hour*
- 4mm spacers as standard
- T, straight, and cross configurations

*In a controlled environment. Weather conditions may vary performance. Test report available to download at www.rynosystems.com



Details

Material	Polypropylene
Spacer tab thickness	4mm

Part Information

Description	Suitable paving interface	Pack quantity
4mm Cross Spacer	20mm Porcelain	25
4mm T Spacer		
4mm Straight Spacer		

Compatible Components

	RST		PT-QU
	Aluminium Paving Support Rail		Quadro Porcelain Paver

Got questions? Give us a shout.

Visit www.rynosystems.com or call us today on **+44 (0)203 967 3500** or reach out on sales@rynosystems.com