

BT

Aluminium Base Track



Overview

The Aluminium Base Track is a fully non-combustible base track designed to be compatible with all Ryno Linear Track and Vantage Juliet systems. The base track is made from structural grade aluminium 6005A T6, coated in Qualicoat Class 2 powder coating for superior durability. It features a 7 degree top surface to promote water flow away from the building structure. Each track provides a neat aesthetic, with hidden fixings.



- Non-combustible
- Qualicoat Class 2 powder coating
- 4 options for different scenarios
- Hidden fixings

Details

Material	Aluminium 6005A T6
Coating	Interpon D2000 series, Qualicoat Class 2 powder coating (non textured)

Performance

Reaction to fire (BS EN 13501-1)	A2-s1, d0
Allowable load	See System data
Biological and chemical	Resistant to moulds, algae, alkali, bitumen, UV
Warranty	12 years*
Design life	60 years

*assembled product warranty



Fixing Information

Description	Driver size	Use case
Screw, Taptite Torx Pan Head, A2 stainless steel, M8 x 30mm	TX30	Fix through base track into infill bar
Aluminium Washer Plate	n/a	Insert into BTa Base Track to fix to substrate
M16x50 Hexset bolt and Nyloc Nut	HX M16	Fixing BTa Base Track to substrate e.g. BaseLink

Got questions? Give us a shout.

Visit www.rynosystems.com or call us today on **+44 (0)203 967 3500** or reach out on sales@rynosystems.com

Finishes

			
RAL 8019 - Grey Brown	RAL 7016 - Anthracite Grey	RAL 7037 - Dusty Grey	RAL 7039 - Quartz Grey
			
RAL 7040 - Window Grey	RAL 8014 - Sepia Brown	Custom RAL colour options	

Compatible Components

	IB Aluminium Infill Bar		BL BaseLink Balustrade Connection
---	-----------------------------------	--	---

Got questions? Give us a shout.

Visit www.rynosystems.com or call us today on **+44 (0)203 967 3500** or reach out on sales@rynosystems.com