

# CDS Cantilever Deckboard Support



## Overview

The Cantilever Deckboard Support is specifically designed for remediation projects to support deckboards that need to bridge a gap between the vertical façade of a building and the steelwork of a balcony, when the decking needs to be adjacent to the building façade. It is designed to provide up to 100mm of cantilever support. Made from 6063-t6 aluminium, an inherently non-combustible material, it is compatible with all RYNO BalcaSmart Aluminium Deckboards.



- Innovative problem-solving solution
- Ideal for remediation projects
- Inherently non-combustible

## Details

<b>Material</b>	Aluminium 6063-T6
<b>Dimensions</b>	Supports up to 100mm cantilever 75mm width 75mm height
<b>Weight</b>	0.129kg

## Performance

<b>Reaction to fire (BS EN 13501-1)</b>	Inherently A1 (Decision 94-611/EC)
<b>Maximum spacing</b>	Determined by board span - see relevant datasheet
<b>Biological and chemical</b>	Resistant to moulds, algae, alkali, bitumen, UV
<b>Warranty</b>	30 years*

\* When installed as part of a complete RYNO system

**Got questions? Give us a shout.**

Visit [www.rynosystems.com](http://www.rynosystems.com) or call us today on **+44 (0)203 967 3500** or reach out on [sales@rynosystems.com](mailto:sales@rynosystems.com)

### Compatible Components

	<p><b>DFB-DR</b> Aluminium Decking Board - Direct Fix with Drainage</p>		<p><b>DFB</b> Aluminium Decking Board - Direct Fix</p>
	<p><b>HHS</b> Hex-head Screw</p>		

**Got questions? Give us a shout.**

Visit [www.rynosystems.com](http://www.rynosystems.com) or call us today on **+44 (0)203 967 3500** or reach out on [sales@rynosystems.com](mailto:sales@rynosystems.com)