

SGP

Soffit Gutter Profile



Overview

The Soffit Gutter is typically fitted on the edge of the balcony soffit and is the primary rainwater collection layer. It is designed to be used with rainwater outlet(s) and overflow within the gutter, which enable connection to the building's drainage system and ensure adequate drainage of the balcony. It is used with the edge profiles and soffit boards to create a complete positively drained soffit. It is made from high strength aluminium 6063 T6 and has a powder coated finish to match other components of the soffit.



- Compatible with Positive Drainage system
- Manufactured from high strength aluminium 6063 T6
- Powder coated finish

Details

Material	Aluminium 6063-T6
Dimensions	40x120x3600mm
Weight	2.7kg/m
Coating	Qualicoat 'Seaside' Class 2 powder coating

Performance

Reaction to fire (BS EN 13501-1)	A2-s1, d0
Biological and chemical	Resistant to moulds, algae, alkali, bitumen, UV
Warranty	30 years*
Design life	60 years

*When used as part of a complete RYNO system





Part information

Fixing details**	To steel: M8 x 150mm carriage bolt + 2x hex nuts To SEC Edge Closure Profile: Horizontal Corner Bracket To ASB Soffit Board (at corners): 4.8x10mm sealed pop rivets stainless steel A2 To ASB Soffit Board (to adjacent board): PHS 4.8x13mm Pan head screw
**Fixings supplied separately	

Got questions? Give us a shout.

Visit www.rynosystems.com or call us today on **+44 (0)203 967 3500** or reach out on sales@rynosystems.com

Finishes

			
RAL 7016 Anthracite Grey	RAL 7037 Dusty Grey	RAL 7039 Quartz Grey	RAL 7040 Window Grey
			
RAL 8014 Sepia Brown	RAL 8019 Grey Brown	Other RAL colours available on request	

Compatible Components

	AF-SB Aluminium Frame Soffit Board		SEC-F Soffit Edge Closure Profile
	AFL-SB Aluminium Frameless Soffit Board		

Got questions? Give us a shout.

Visit www.rynosystems.com or call us today on **+44 (0)203 967 3500** or reach out on sales@rynosystems.com