

# CDB-P

## Performance Composite Decking Board

### Overview

The Performance Composite Decking Board is a wood-polymer composite (WPC) board with a contemporary, grooved appearance, ideal for achieving a classic composite look. This Class B fire rated board is reversible, providing both narrow and wide groove options, offering greater design possibilities, along with a matching corner profile for the edge of decked areas.

- 5 colour options, 10 different looks
- Class B fire rated
- Long-lasting: will not rot, warp, or twist
- Non-slip and splinter-proof
- Low maintenance: no need for treatment or staining
- Matching corner profile



### Details

<b>Material</b>	Wood-polymer composite (WPC)
<b>Dimensions</b>	3600x150x25 mm
<b>Weight</b>	9.64kg per board






### Performance

<b>Slip resistance (BS EN 7976)</b>	PTV (Dry) $\geq$ 70 PTV (Wet) $\geq$ 50
<b>Allowable load</b>	See “Compatible system” data
<b>Maximum span</b>	400mm
<b>Biological and chemical</b>	Resistant to moulds, algae, alkali, bitumen, UV
<b>Warranty</b>	10 years
<b>Reaction to fire (BS EN 13501-1)</b>	Bfl - s1










### Part Information

Name	Length	Width	Height
<b>Corner Profile</b>	3600mm	54mm	40mm

**Finishes**

			
<b>Dawn</b>	<b>Noon</b>	<b>Dusk</b>	<b>Twilight</b>
			
<b>Midnight</b>			

## Compatible Components

	<p><b>DS</b> Aluminium Joist</p>		<p><b>DSB</b> Decking Screw</p>
	<p><b>DST</b> Decking Screw for Timber</p>		<p><b>RDA</b> Self-levelling Adjustable Joist Support Pedestal</p>
	<p><b>RDA-C</b> Self-levelling Adjustable Joist Support Pedestal with Clip-on Head</p>		<p><b>RDF</b> Fixed Head Adjustable Joist Support Pedestal</p>
	<p><b>RDC-A</b> Adjustable Joist Cradle</p>		<p><b>RDC-F</b> Fixed Height Joist Cradle</p>
	<p><b>CTC</b> Decking T-Clip - Composite</p>		

**Got questions? Give us a shout.**

Visit [www.rynosystems.com](http://www.rynosystems.com) or call us today on **+44 (0)203 967 3500** or reach out on [sales@rynosystems.com](mailto:sales@rynosystems.com)